

# WAXED & OILED WOOD FLOOR MAINTENANCE

## PRODUCT DESCRIPTION

- Blanchon WAXED & OILED WOOD FLOOR MAINTENANCE is the natural partner to Blanchon HARD WAXOIL.
- WAXED & OILED WOOD FLOOR MAINTENANCE contains natural raw materials. It has high wax content giving an excellent waxing power. It penetrates to the core of solid wood, plywood and cork floors for long-lasting protection, while preserving the wood's natural appearance and elasticity. It is only suitable for interior use. (Do not use outdoors.)
- WAXED & OILED WOOD FLOOR MAINTENANCE has a pleasant, subtle fragrance of natural wax and complies with the European Toy Safety Standard EN 71.3.
- WAXED & OILED WOOD FLOOR MAINTENANCE is easy to apply on all commonly used woods which have been protected with HARD WAXOIL.
- WAXED & OILED WOOD FLOOR MAINTENANCE is available in a natural finish.

## THE "LONG TRADITION" RANGE

- WAXED & OILED WOOD FLOOR MAINTENANCE is part of a range of Blanchon products specially designed to care naturally for parquets, wood floors and woodwork.
- Based on natural raw materials, this range is easy to apply, enables simple and convenient maintenance and gives wood floors a natural appearance in keeping with long-standing traditions:

WOOD FLOOR OIL,  
WOOD FLOOR OIL - SPECIAL MAINTENANCE,  
LIQUID WAX,

NATURAL SOAP FOR OILED WOOD FLOORS,

NATURÖL MAINTENANCE,  
HARD WAXOIL,  
WAXED & OILED WOOD FLOOR  
MAINTENANCE,  
PROFESSIONAL FLOOR POLISH.

## SUBSTRATE PREPARATION

- WAXED & OILED WOOD FLOOR MAINTENANCE is specially designed to care for wood floors and parquets treated with HARD WAXOIL.
- WAXED & OILED WOOD FLOOR MAINTENANCE should be applied on a clean, dry floor: always remove all traces of dust beforehand (using a brush, vacuum cleaner, etc.).
- Ordinary stains and marks can easily be removed with a neutral detergent (using a damp cloth or mop, never a soaking wet one). NB: Wait 2 weeks before applying WAXED & OILED WOOD FLOOR MAINTENANCE for the first time to give the HARD WAXOIL time to fully harden.
- Stubborn marks, stains or scratches can be removed by fine sanding followed by an application of HARD WAXOIL.

NB: See appendix for regular cleaning of waxed/oiled wood floors (on the next page).

- Important: On wood that has been stained or dyed with coloured HARD WAXOIL (or previously stained wood), the traffic on the wood floor will determine how the shade evolves over time. Wood floor maintenance should be done regularly and thoroughly to ensure long-lasting protection and decoration.

## DIRECTIONS FOR USE

- WAXED & OILED WOOD FLOOR MAINTENANCE is ready to use. Shake well before use and do not dilute. Stir regularly during use. Do not apply if the temperature is below 12°C. Only use in well ventilated areas. Do not leave plants and aquariums in contact with the solvent vapours.
- Spray WAXED & OILED WOOD FLOOR MAINTENANCE (using a hand sprayer) onto the clean, dust-free floor and wipe very regularly as you apply with a clean, dry, cotton cloth until a matt finish is obtained. The coat should be very thin, around 20 to 25m<sup>2</sup> per litre. It is easier to work on one small area at a time. Localised, small repairs may be done by directly applying and polishing with a cotton cloth.
- A polishing machine with 3 revolving brushes or a heavy duty buffing machine fitted with a beige pad makes application easier. This is then similar to a spray method: buffing is quicker and mechanical cleaning more effective.
- buffing (with a cotton cloth or buffing machine) as you apply gives wood treated with HARD WAXOIL an even, attractive appearance without leaving any surface residue.
- Frequency: Whenever the wood floor loses its beautiful finish, generally once or twice a month.
- On high-traffic wood floors, regular maintenance can be backed up by applying a general coat of HARD WAXOIL, followed by careful hand or machine polishing.
- The more WAXED & OILED WOOD FLOOR MAINTENANCE is used, the easier maintenance becomes.

PROPERLY MAINTAINED WAXED/OILED WOOD FLOORS LOOK BETTER AND BETTER AS TIME GOES BY.



Contains  
Vegetable Oils  
and Natural Waxes



Dust proof



Quick drying



Natural finish



Creamy texture



The Blanchon logo, featuring the brand name in a white, stylized, cursive font on a dark blue rectangular background.

## WAXED & OILED WOOD FLOOR MAINTENANCE

### TOOL CLEANING

- Clean tools immediately after use with Blanchon ODOURLESS THINNER.
- Clean cloths, pads and tools immediately after use (risk of self ignition with oil-soaked fabrics). Cloths and pads may also be left in water. Do not dispose of oil-soaked pads and cloths without first rinsing them in water.
- Do not pour down the drain.

### DRYING

- Dust-free: Around 4 to 6 hours at 20°C.
- Normal use of the area: 12 to 24 hours after application and buffing.
- Light traffic: 4 to 6 hours after buffing.

### COVERAGE

- 20 to 25 m<sup>2</sup> per litre per coat.

### STORAGE

- At least 1 year in the original unopened container.
- Seal the container properly after use.

## TECHNICAL DATA

<b>USE</b>	MAINTENANCE OF WOOD FLOORS AND PARQUETS TREATED WITH HARD WAXOIL
<b>RESIN TYPE</b>	Natural waxes and resins
<b>AFNOR CLASSIFICATION</b>	Family I, class 2b
<b>DENSITY</b>	0.86 (at 20°C, as per N F T 30020)
<b>FLUIDITY</b>	Around 35 seconds (ISO Cup n°4 at 20°C)
<b>REGULATORY INFORMATION</b>	Refer to the relevant Safety Data Sheet (also available on <a href="http://www.blanchon.com">www.blanchon.com</a> or <a href="http://www.quickfds.com">www.quickfds.com</a> )
<b>RESISTANCE TO HOUSEHOLD PRODUCTS</b>	Vegetable oil, acetone, 40° alcohol, water, coffee, tea, ink: no adverse effects found (after 20 days' drying, as per N F T 30053).

### APPENDIX 1: REGULAR CLEANING OF WAXED/OILED WOOD FLOORS

- Clean with a damp mop using Blanchon NATURAL SOAP FOR OILED WOOD FLOORS (250 ml diluted in 10 litres of water).
- Work on one small area at a time, rinsing the cloth or mop regularly: it should always be well wrung out to avoid getting the wood floor too wet.
- Frequency: from once a week on light-traffic floors to daily cleaning on heavy-traffic floors. NATURAL SOAP FOR OILED WOOD FLOORS, which is 100% natural, is ideal for cleaning waxed/oiled wood floors thoroughly and boosting their protection.
- Wipe down any water spillages immediately on floors treated with HARD WAXOIL

### APPENDIX 2: REFINISHING

- **REFINISHING SMALL AREAS** : : For small areas with specific damage (cigarette burns, impact damage, etc.) rub or scrape to remove the damage and then reapply. This is one of the great advantages of a wood floor treated with HARD WAXOIL..
- **REFINISHING LARGE AREAS** : On waxed/oiled wood floors that have not been maintained for as frequently as their use requires, a general sanding can be done using a buffing machine fitted with a sanding disc (about 120 grit) before applying a coat of undiluted HARD WAXOIL (using a brush, a graining brush, a short haired roller or spraying). Polish by hand or with a buffing machine

Technical Data Sheet issued by the Documentation Department on 25.02.2003, validated by the Technical Department on 21.02.2003 and the Sales Department on 04.02.2003  
Designed and made in France.

The information provided in this Technical Data Sheet is given in good faith for information purposes only.  
In no case whatsoever can this information be considered as a guarantee nor engage our responsibility when our products are used.  
This Technical Data Sheet cancels and supersedes all previous versions.

BLANCHON S.A. - Société anonyme  
à directoire et conseil de surveillance  
au capital de 4 258 258 €  
RCS LYON 390 112 886 - APE 243 Z  
CCP 196.03 F LYON

E-mail : [info.uk@blanchon.com](mailto:info.uk@blanchon.com)  
Site internet : [www.blanchon.com](http://www.blanchon.com)



28, rue Charles Martin - BP 105  
69192 SAINT-FONS CEDEX (France)  
Tél. 04 72 89 06 00  
Fax 04 78 70 07 18

Export Direct Lines  
Tél : (0033) 472 89 06 09  
Fax : (0033) 472 89 06 02